

(1) Type Examination Certificate

(2) No. of the Type Examination Certificate: **ZP/B058/19**

(3) Product: **Anchor device type A**
Type: **KIT BOX**

(4) Manufacturer: **INNOTECH Arbeitsschutz GmbH**

(5) Address: **Laizing 10, 4656 Kirchham, Austria**

(6) The design of this product and any acceptable variation thereto are specified in the schedule to this Type Examination Certificate.

(7) The certification body of DEKRA Testing and Certification GmbH certifies that this product complies with the fundamental requirements of the standard listed under item 8 below. The examination and test results are set out in the report PB 19-065.

(8) The requirements of the standard are assured by compliance with

DIN EN 795:2012

DIN CEN/TS 16415:2017


(9) This Type Examination Certificate relates only to the design, examination and tests of the specified product in accordance to the standard list. Further requirements of the Directive apply to the manufacturing process and supply of this personal protective equipment. These are not covered by this certificate.

(10) This Type Test Certificate is valid until 2024-03-25.

DEKRA Testing and Certification GmbH
Bochum, 2019-03-26

signed: Kilisch
Managing director

We confirm the correctness of the translation from the German original.
In the case of arbitration only the German wording shall be valid and binding.


Managing director

TRANSLATION

- (11) Appendix to
- (12) **Type Examination Certificate
ZP/B058/19**
- (13) 13.1 Subject and Type
Anchor device type A
Type: KIT BOX

13.2 Description

The anchor device type C of type KIT BOX (Fig. 1) is used to temporarily protect a maximum number of four people against falls from a height. The anchor line of the anchor device consists of a wire rope (8 mm diameter in the variant 7 x 7).

The anchor device is fastened to the respective end anchors. The wire-rope anchor line is fastened at the respective end anchors by means of the clamping devices provided.

The user connects his personal protective equipment against falls from a height by means of a connecting element according to EN 362.

Optionally, an intermediate anchor can be used as well. It is not possible to override the intermediate anchor.

The anchor device is mounted horizontally either to suitable surfaces of sufficient strength using the intermediate and end anchors of type AIO-ENDS-50/-51 or directly to the structure using the anchor devices provided. It is not possible to override the end anchors. The pre-tensioning of the flexible anchor line is 1.0 kN and a maximum distance of 15 m between two anchors (between end and intermediate anchors or end anchors) shall not be exceeded.

The metallic components of the anchor device are made of corrosion-resistant steel.



Fig. 1: Anchor device, type: KIT-BOX

- (14) Report
PB 19-065, 2019-03-26