

## FS243.06 SPIDER™ EVO




The **FALL SAFE® FS243.06 - SPIDER™ EVO** has 12 adjustment points, including unique ventral and vertical legs extension adjustment. Instead of the usual D-Rings, FS243.06 has O-Rings, coming from the evolution of the standard SPIDER™. This harness has dense yet narrow legs in order to allow more comfort to the user when working.

The airflow through all the harness layers is assured by the new and improved Croc™ SPIDER™ 2.0 padding. This innovation also allows for a lighter and more ergonomic final product, that is extremely comfortable for several hours in suspension.

With reflective and extra breathable fabric, the FS243.06 combines the lightness of its composition with the FALL SAFE® quality assurance.



Ownership of this design is registered and protected, and any unauthorized duplication or distribution of this design could result in prosecution.

EAN CODE	SIZE	WEIGHT (KG)	APPLICATIONS
5605423800623	S/M	1,2	Arborist   Rescue   Confined Spaces   Wind Turbines   Rope Access   Riggers 
5605423800630	L/XL	1,3	
5605423800647	XXL	1,4	
INTENSITY OF USE			STANDARDS
Intensive use 			 EN358:1999 EN361:2002 EN813:2009

## FS243.06 SPIDER™ EVO

### FEATURES



### PHYSICAL PROPERTIES

Metal parts	Aluminium
Webbing	PES HP Water repellent
D-Rings	Dorsal D-Ring attachment point Chest O-Ring attachment point 2 Lateral O-Rings attachment points Ventral D-Ring attachment point
Buckles	IZY Quick connect buckles
Padding	Croc™ SPIDER™ EVO 2.0
Adjustment points	12 points
Fall arrest indicators	Yes

### OTHER INFORMATION

Device lifespan	10 years
Max. Load	<140 KG
Inspection requirement	Yearly
Traceability	Serial Number/ RFID/ QR Code
Manual Instructions	<a href="http://www.fallsafe-online.com">www.fallsafe-online.com</a>   +351 252 480 060