

TECHNICAL DATA SHEET

FS930E FS930E SHARP EDGE SERIES

The **FALL SAFE® FS930E** - **SHARP EDGE SERIES** is a lightweight, durable and compact fall arrest block. It has two aluminium alloy connectors and a energy absorber integrated. The retractable system is composed by a 25 mm dyneema webbing inserted in a plastic housing. This block is sharp edge tested. There are 3 connectors combinations.



EAN CODE	COMBINATION	LENGTH (M)	~WEIGHT (KG)	STANDARDS
5605423801088	BC	2,0	1,552	
5605423801095	ТВ	2,0	1,502	CE EN360:2002
5605423801101	TC	2,0	1,138	CNB/P/11.060
APPLICATIONS				
	Scaffolding Access pla	atforms		



TECHNICAL DATA SHEET

FS930E FS930E SHARP EDGE SERIES

FEATURES



PHYSICAL PROPERTIES		
Metal parts	Aluminium	
Housing	Impact resistant glass filled nylon	
Chassis	Stainless and carbon steel	
Webbing	Dyneema® abrasion resistant webbing	
OTHER INFORMATION		
Device lifespan	10 years	
User weight	<120 Kg (1 person use)	
Inspection requirement	Yearly	
Traceability	Serial Number/ RFID/ QR Code	
Manual Instructions	www.fallsafe-online.com +351 252 480 060	

FALL SAFE® - Zona Industrial da Varziela, Rua B, Lote 54, 4480-620 Vila do Conde, PORTUGAL | Tel.: +351 252 480 060 | Fax.: +351 252 480 069 | Website: www.fallsafe-online.com Copyright © 2020-2021 FALL SAFE®, All rights reserved. All pictures shown are for representation purpose only. Actual product may vary due to product enhancement. Products and specifications subject to change without notice.